



- NOTES:
- MATERIAL
 - INSULATOR:PBT+30%GF BLACK
 - CONTACT:BRASS
 - CONTACT PLATING:GOLD/TIN PLATED
 - SHELL:SPCC, NICKEL PLATED
 - SCREW:BRASS,NICKEL PLATED

- 2.SPECIFICATION
- CURRENT RATE:5AMPS
 - INSULATOR RESISTANCE:1000Ω MIN,AT 500V DC
 - DIELECTRIC STRENGTH:1000V PER MINUTE
 - OPERATION TEMPERATURE:-55°C TO +105°C

To prepare:

PART NO.	RIVETING STRUCTUER	SCREW	CONTACT PLATING
20340-15RS1	鍍合不附螺絲		GOLD/TIN PLATED
20340-15RS2	鍍合鍍螺絲	4.8*11.8	GOLD/TIN PLATED
20340-15RS3	叉鍍鍍螺絲	4.8*11.8	GOLD/TIN PLATED
20340-15RS4	鍍合附螺絲	4.8*11.8	GOLD/TIN PLATED
20340-15RS5	鍍合附螺絲	5.8*12.8	GOLD/TIN PLATED
20340-15RS6	鍍合鍍螺絲	5.8*12.8	GOLD/TIN PLATED
20340-15RS7	鍍合附螺絲	5.8*11.8	GOLD/TIN PLATED
20340-15RS8	鍍合鍍螺絲	5.8*11.8	GOLD/TIN PLATED

尚益科技有限公司

PROJ	SCALE	F	MOLD NO	20340-15RS
	DO NOT SCALE	DWG		
APP	CHK	DGN	DRW	
HSIEH	HSIEH	HSIEH	HSIEH	
2018.05.29	2018.05.29	2018.05.25	2018.05.25	
MODEL	FILE NO	UNIT	SHT 1 OF 1	REV. X1
		MM		SIZE A4

DIMENSIONS TOLERANCE METRIC
 .0= ±.38
 .00= ±.25
 .000= ±.15
 ANG.= ± 2°

P.C.B. LAYOUT(TOLERANCE±0.05)
 TOP VIEW

尚益科技有限公司