



P.C.B. LAYOUT (TOLERANCE ±0.05)  
TOP VIEW

- NOTES:
- MATERIAL
    - Insulator: PBT4830 (UL94V-0)
    - Contact: Brass
    - Contact Plated: Gold/TIN PLATED
    - Shell: Steel, Nickel Plated
    - Screw: Brass, Nickel Plated
  - SPECIFICATION
    - Current Rate: 1 Amps
    - Insulator Resistance: 1000MΩ Min. At 500V DC
    - Dielectric Strength: Test between adjacent contacts At 500V AC(rms) and 60 seconds hold time
    - Operation Temperature: -55°C to +105°C

\*\*標示是重點管控尺寸

DIMENSIONS  
TOLERANCE  
METRIC  
0= ±.38  
.00= ±.25

PART NO.	PLATING	COLOR
20340-RP X-1	GOLD/TIN PLATED	GREEN
20340-RP X-2	GOLD PLATED	BLACK
20340-RP X-3	GOLD/TIN PLATED	BLACK

**尚益科技有限公司**  
JMSCONN TECHNOLOGY CO., LTD.

PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO <b>20340-9RP1X</b>
APP	MODEL	FILE NO
CHK	2016.03.24	REV. X1
DGN	UNIT	SIZE
DRW	MM	A4
		SHT 1 OF 1