



NOTES:

- 1.MATERIAL
 1.1 Insulator:PBT+30%Glass Fiber(UL94V-0)
 1.2 Contact:Brass
 1.3 Contact: Gold Plated
 1.4 Shell:Steel Nickel Plated
 1.5 Screw: Brass ,Nickel Plated
- 2.SPECIFICATION
 2.1 Current Rate:3 Amps
 2.2 Insulator Resistance:1000MΩMin.
 2.3 Dielectric Strength:500V AC Per minute
 2.4 Operation Temperature:-40°C to+85°C
 2.5 Contact Resistance:30mΩMax

To prepare:

PART NO.	RIVETING STRUCTUER	SCREW	CONTACT PLATING
20341-15DP1	铆合不附螺絲		Gold Plated
20341-15DP2	铆合鎖螺絲	4.8*11.8	Gold Plated
20341-15DP3	铆合附螺絲	4.8*11.8	Gold Plated

尚益科技有限公司 JMSSCONN TECHNOLOGY CO., LTD.				
PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO 20341-15DP		
APP		MODEL	FILE NO	REV. X1
CHK				
DGN		UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2018.9.26	MM	

DIMENSIONS TOLERANCE
 METRIC
 .0= ±.5
 .00= ±.30
 .000= ±.20
 .0000= ±.
 ANG.= ± 2°

P.C.B. LAYOUT(TOLERANCE±0.05)
 TOP VIEW