



SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:
 Contact Current Rating: 1m Amperes.
 Dielectric Withstanding Voltage: DC 500V/60sec.r.m.s
 Insulation Resistance: 1000 Megohms Minimum at DC 500V.
 Contact Resistance: 50 Milliohms Maximum.
 Operating Temperature: -45°C to +85°C.

MECHANICAL CHARACTERISTICS:
 Contact Insertion Force: 4.5kg Maximum.
 Contact Separation Force: 0.4kg minimum.

MATERIALS:
 Contacts: Brass.
 Insulator: PBT UL 94V-0 Rated.
 Shell: Cold Roller Steel.
 Harpoon: Brass.
 Rivet: Copper alloy

FINISHES:
 Contact: Ni Tin plated & Gold Flash.
 Shell: Nickel Plated.
 Harpoon: Ni, Tin Plating.
 Rivet: Ni, Tin Plating

DIMENSIONS TOLERANCE

METRIC
.0=±0.38
.00=±0.25
.000=±0.15
ANG.=±2°

注意: *為重點管控尺寸.

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.				
PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	20342-T	
APP		MODEL	FILE NO	REV. X1
CHK				
DGN		UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2013.09.22	MM	