



P.C.B LAYOUT  
BOTTOM VIEW (pcb:Tolerance $\pm 0.05$ )

NOTES:  
 SHELL:SPCC,T=0.40mm,NICKEL PLATED,  
 HOUSING: PBT 30%G.F, UL94V-0,COLOR:BLACK  
 COVE: NYLON 9T, UL94V-0,COLOR:BLACK  
 CONTACT MATERIAL:BRASS ,PLATING:GOLD/TIN FINISHED  
 HARPOON:BRASS ,PLATING:TIN FINISHED  
 JACK SCREWS:BRASS MATERIAL,NICKEL FINISHED  
 WITH #4-40 THREADED ATTACHED

ELECTRICAL CHARACTERISTICS  
 CONTACT CURRENT RATING: 5.0 AMPS  
 CONTACT RESISTANCE: 30m OHMS MAX  
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC PER MIN  
 INSULATION RESISTANCE: 1000M OHMS MIN  
 TEMPERATURE RATING: -55 $\phi$ C~+105 $\phi$ C  
 \*\*標示是重點管控尺寸

成品料號	螺絲料號	螺絲材質	鐵殼型號
20344-T-0927	20344-T *1000N	BRASS	48H

DIMENSIONS TOLERANCE METRIC  
 .0=  $\pm .38$   
 .00=  $\pm .25$   
 .000=  $\pm .15$   
 .0000=  $\pm .$   
 ANG.=  $\pm 2^\circ$

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.				
PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	20344-T	
APP		MODEL	FILE NO	REV. X1
CHK				
DGN		UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2013.09.22	MM	