



NOTES:

1.MATERIAL:

- 1.1 Insulator:PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact: Brass
- 1.3 Contact Plated: Gold or Tin Plated
- 1.4 Shell: Steel, Nickle Plated
- 1.5 SCREW: BRASS, Nickle Plated

2.SPECIFICATION:

- 2.1 Current Rate: 5 Amps
- 2.2 Insulator Resistance: 1000M Min. at 500V DC
- 2.3 Dielectric Strength: 500V Per minute
- 2.4 Operation Temperature: -55°C to +105°C
- 2.5 Contact Resistance:30m Ohms Max

*" 標示是重點管控尺寸

PART NO	PLATED	專用紙箱
20348-T2-6980	GOLD/TIN PLATED	KSD
✓ 20348-T2-6983	GOLD/TIN PLATED	SPG

DIMENSIONS TOLERANCE
 METRIC
 .0=±0.38
 .00=±0.25
 .000=±0.15
 ANG.=±2°

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.				
PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO 20348-T2		
APP		MODEL	FILE NO	REV. X1
CHK				
DGN		UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2013.09.22	MM	