



MATERIAL:
 HOUSING:P.B.T
 CONTACT: COPPER ALLOY
 BOARD LOCK: SPCC
 SQUARE RIVET: COPPER ALLOY
 SHELL: STEEL

ELECTRICAL CHARACTERISTICS:
 RATED CURRENT:5A
 RATED VOLTAGE: 250V DC
 INSULATION RESISTANCE:1000M OHMS MIN.AT 500VDC
 CONTACT RESISTANCE: 30m OHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC FOR ONE MINUTE

FINISH:
 SHELL: NICKEL PLATED
 CONTACT GOLD PLATED IN CONTACT AREA TIN PLATED IN SOLDER AREA.
 BOARD LOCK: NICKEL PLATED
 SQUARE RIVET: NICKEL PLATED
 OPERATING TEMPERATURE: -55°C TO +85°C

***標示是重點管控尺寸

PART NO.	COLOR
20363-T -1258S	GREEN
20363-T -1208S	BLACK

DIMENSIONS TOLERANCE
METRIC
 .0= ±.38
 .00= ±.25
 .000= ±.XXX
 .0000=±
 ANG.= ± 2'

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.				
PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	20363-T	
APP		MODEL	FILE NO	REV. X1
CHK				
DGN		UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2013.09.22	MM	