



SPECIFICATIONS:

- 1.INSERTION FORCE:3.0KG MAX. WITHDRAWAL FORCE:1.0KG~3.0KG
- 2.INSULATION RESISTANCE BETWEEN ANY ADJACENT TERMINALS SHALL NOT BE LESS THAN 100 MEGOHMS BY 500 VOLTS MEGGER
- 3.JACK SHALL WITHSTAND 250 VOLTS BETWEEN ANY ADJACENT TERMINAL FOR ONE MINUTE.
- 4.CONTACT RESISTANCE SHALL NOT EXCEED 30mΩ
- 5.JACK SHALL WITHSTAND 5000 CYCLES OF INSERTION AND WITHDRAWAL WITH TESTING PLUG,AND CONTACT RESISTANCE SHALL NOT EXCEED 30mΩ
- 6.MEASURING CONDITION:
TEMPERATURE:FROM 5°C TO 35°C
RELATIVE HUMIDITY:FROM 40% TO 85%.
- 7.ENVIRONMENTAL SPECIFICATIONS:
7.1 HUMIDITY TEST:HUMIDITY 90% TO 95% TEMPERAUER 40°C±2°C FOR 96 HOURS
7.2 HEAT TEST:TEMPERATURE 70°C ± 2°C(HUMIDITY BELOW50%) FOR 96 HOURS.
7.3 COLD TEST:TEMPERATURE -40°C ± 2°C FOR 96 HOURS.
- 8.PACKAGING:TRAY
- 9.PRINTED DATE CODE*YYYYMMDD*ON TOP OF CONNECTOR.

注意:帶*為重點檢驗尺寸。

F	GROUND	1	STAILESS 0.15t	N/A
E	SHELL	1	SPCC-SD 0.40t	Nickel 60u" Overall
D	STOPPER	1	PA9T, UL 94V-0 Halogen-free	BLACK
C	PIN	1	BRASS	Ag:20u" Min on Contact Area Cu:60u" Min On Sdder Ni:60u"
B	SPRING	1	PHOSPHOR BRONZE 0.30t	Sn:60u" Min on Contact Area Cu:60u" Min On Sdder Ni:60u"
A	HOUSING	1	PA9T, UL 94V-0 Halogen-free	BLACK
NO.	DESCRIPTION	QTY	MATERIAL	PLATING&COLOR

尚益科技有限公司
JMSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 35361
APP			MODEL
CHK			FILE NO
DGN			REV. X1
DRW	HSIEH	2016.11.18	UNIT MM
			SHT 1 OF 1
			SIZE A4