



- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
 - 1-1. RATING:
 - 1-2. CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500V DC
 - MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE : 0.3~3.0 KGF
 - 2-2. WITHDRAWAL FORCE : 0.3~3.0 KGF
 - LIFE TEST: 5,000 CYCLES MIN.
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 - * REPRESENT CRITICAL DIMENSIONS.

NO.	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
⑦	HOUSING	1	PA9T	Black
⑥	TERMINAL 6#	1	PHOSPHOR BRONZE t=0.20	Au-plated
⑤	TERMINAL 5#	1	PHOSPHOR BRONZE t=0.20	Au-plated
④	TERMINAL 4#	1	PHOSPHOR BRONZE t=0.20	Au-plated
③	TERMINAL 3#	1	PHOSPHOR BRONZE t=0.20	Au-plated
②	TERMINAL 2#	1	PHOSPHOR BRONZE t=0.20	Au-plated
①	TERMINAL 1#	1	PHOSPHOR BRONZE t=0.20	Au-plated

DIMENSIONS TOLERANCE METRIC
 .05 = ±.38
 .00 = ±.25
 .000 = ±.15
 .0000 = ±.
 ANG. = ± 2°

尚益科技有限公司
 JMSCONN TECHNOLOGY CO., LTD.

PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	38731-T	
APP		MODEL	FILE NO	REV. X1
CHK		UNIT MM	SHT 1 OF 1	SIZE A4
DGN				
DRW	HSIEH	2013.09.22		