



RECOMMEND P.C.B. LAYOUT
BOTTOM VIEW

- MATERIALS**
- HOUSING : THERMOPLASTIC (UL 94V-0).
 - TERMINAL : COPPER ALLOY, TIN/NI PLATING
 - FRONT SHIELD : STEEL, NICKEL PLATING
 - BACK SHIELD : STEEL, NICKEL PLATING
- SPECIFICATION**
- CURRENT RATING : 0.3 AMP. MAX.
 - DIELECTRIC WITHSTANDING : AC 500V/min R.M.S.
 - INSULATION RESISTANCE : 1000M Ω min. AT 500V DC.
 - CONTACT RESISTANCE : 50m Ω MAX.
 - OPERATING TEMPERATURE : -25°C TO +85°C.
 - DURABILITY : 5000 CYCLES.
 - MATING FORCE : 5kgs MAX
 - UNMATING FORCE : 0.4~3.0kgs
 - MAX PROCESSING TEMPERATURE : 230°C FOR 30~60 SECONDS. (HI.-TEMP. PLASTIC)
- * * 標示是重要尺寸

DIMENSIONS TOLERANCE
METRIC
.0 = \pm .5
.00 = \pm .30
.000 = \pm .15
.0000 = \pm .1
ANG. = \pm 2'

尚益科技有限公司 JMSSONIN TECHNOLOGY CO., LTD.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO	39003-T	
APP			MODEL	FILE NO	REV. X1
CHK					
DGN			UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2016.11.21	MM		