


$2.54$   
 $2.54 \times (\text{No. of Contacts} - 1)$   
 $0.5 + 2.54 \times \text{No. of Positions.}$

Specifications  
 Current Rating: 3 AMP  
 Insulator Resistance: 5000MΩ Min  
 Dielectric Withstanding: 500V AC  
 Contact Material: Copper Alloy  
 Operating Temperature: -40°C to +105°C  
 Insulator Material: Polyester (UL94V-0)  
 ◎Standard: P.B.T

FINISH: Gold Plated  
 Standard: Gold Flash all over



Number of Contacts  
 03 to 30 Contacts

12003 -XX X -XX

Contact Plating  
 B: Gold Flash  
 E: 10u" Gold  
 F: 15u" Gold  
 J: 30u" Gold  
 Standard: B

	A	B
1W	11.05	2.30
1Y	11.05	7.35
2Y	13.59	4.85
3Y	16.13	2.30
1Z	11.05	12.2
2Z	13.59	9.65
3Z	16.13	7.10
4Z	18.67	4.60

APPLICATION AND FEATURES  
 1. Different foot length for customer design choice  
 2. Available with square tail.  
 Mating with □0.64 & □0.60 Pin Headers.

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.				
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 12003	
APP			MODEL	FILE NO
CHK				REV. X1
DGN			UNIT	SIZE
DRW	SHIEH	2007.11.06	MM	SHT 1 OF 1 A4