



REQUIREMENTS

- CONTACT RESISTANCE: $30m\Omega$ max. (INITIAL)
- INSULATION RESISTANCE: $100M\Omega$ min. AT 500V DC.
- WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
- SOLDERING HEAT TEST: $260\pm 5^{\circ}C$ FOR 5 ± 1 SECONDS
- INSERTION FORCE: 0.5-4.5KG
- EXTRACTION FORCE: 0.4-3.5 KG
- LIFE TIME: 5000 CYCLES min

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	P.B.T.	BLACK	1	
2	CONTACT	PHOS. BRONZE	GOLD-TIN PLATED	3	N1:1~5u ; TIN:3u GOLD:1~3 u"
3	GROUND	BRASS	TIN PLATED	1	TIN:3~5u.
4	BACK COVER	P.B.T.	BLACK	1	
5	SHIELD	COPPER ALLOY	TIN PLATED	1	TIN:3~5u.

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LED.				
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30001-3-02	
APP			MODEL 3 PIN	FILE NO MINI DIN JACK WITHOUT SHIELD COVER
CHK	CCJ	91.01.16		REV. X1
DGN	AMY	91.01.16	UNIT MM	SIZE A4
DRW	SHIEH	91.01.16	SHT 1 OF 1	