


P.C.B. RECOMMEND LAYOUT
(BOTTOM VIEW)

NOTES:

1. MATERIAL :
 HOUSING : THERMOPLASTIC, GLASS FIBER FILLED
 UL 94V-0 RATED.
 CONTACT : PHOSPHOR BRONZE
 INNER SHIELD : SPCC
 2. FINISH :
 CONTACT : UNDER PLATED 50u" MIN. NICKEL, OVER ALL
 120u" MIN. TIN IN SOLDERING AREA,
 SELECTIVE GOLD PLATED IN CONTACT AREA.
- INNER SHIELD : L: BRIGHT TIN , PLATED WITH 120u" THICK.
 OVER 50u" THICKNESS Ni.
 S: TIN , PLATED WITH 120u" THICK.
 OVER 100u" THICKNESS Cu.
 N: NICKEL , PLATED WITH 120u" THICK.
 OVER 100u" THICKNESS Cu.
 G: GOLD FLASH , OVER 100u" THICKNESS Cu.

尚益科技有限公司 JMSSCONN TECHNOLOGY CO., LED.					
PROJ		SCALE : F	MOLD NO		
		DO NOT SCALE DWG	30001-3-03		
APP			MODEL	FILE NO	REV.
CHK	CCJ	91.01.16			X1
DGN	AMY	91.01.16	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	91.01.16	MM		A4