



REQUIREMENTS
 CONTACT RESISTANCE:30mΩmax.(INITIAL)
 INSULATION RESISTANCE:100MΩmin.AT 500V DC.
 WITHSTANDING VOLTAGE:500V AC FOR ONE MINUTE
 SOLDERING HEAT TEST:260±5°C FOR 5±1 SECONDS
 INSERTION FORCE:0.5-4.5KG
 EXTRACTION FORCE:0.4-3.5 KG
 LIFE TIME:5000 CYCLES min

| NO | NAME | MATERIAL | FINISH | REMARK | Q'TY |
|----|------------|-------------|-----------------|-------------------------------|------|
| 1 | HOUSING | P.B.T | BLACK | | 1 |
| 2 | CONTACT | PHOS.BRONZE | GOLD-TIN PLATED | Ni:1~1.5u TIN:Su Gold:1~3u | 6 |
| 3 | GROUND | BRASS | TIN PLATED | TIN:3~5u | 1 |
| 4 | BACK COVER | P.B.T | BLACK | | 1 |

| 尚益科技有限公司 JMSCONN TECHNOLOGY CO., LED. | | | | | |
|--|-------|-------------------------------|-----------------------|------------|------------|
| PROJ | | SCALE : F DO NOT SCALE DWG | MOLD NO 30001-4-02 | | |
| APP | | | MODEL | FILE NO | REV. X1 |
| CHK | CCJ | 90.06.20 | UNIT MM | SHT 1 OF 1 | SIZE A4 |
| DGN | WU | 90.06.20 | | | |
| DRW | SHIEH | 90.06.20 | | | |