



NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	P.B.T.	BLACK	1	
2	CONTACT	PHOS. BRONZE	GOLD-TIN PLATED	5	N1:1~5u ; TIN:3u GOLD:1~3 u"
3	GROUND	BRASS	TIN PLATED	1	TIN:3~5u.
4	BACK COVER	P.B.T.	BLACK	1	
5	SHIELD	COPPER ALLOY	TIN PLATED	1	TIN:3~5u.

REQUIREMENTS

CONTACT RESISTANCE:30mΩmax.(INITIAL)
 INSULATION RESISTANCE:100MΩmin.AT 500V DC.
 WITHSTANDING VOLTAGE:500V AC FOR ONE MINUTE
 SOLDERING HEAT TEST:260±5°C FOR 5±1 SECONDS
 INSERTION FORCE:0.5-4.5KG
 EXTRACTION FORCE:0.4-3.5 KG
 LIFE TIME:5000 CYCLES min

尚益科技有限公司 JMSSCONN TECHNOLOGY CO., LTD.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30010-5-02		
APP			MODEL 5pin	FILE NO MINI DIN JACK WITH 4 SIDE SHIELD	REV. X1
CHK	CCJ	91.02.22	UNIT MM	SHT 1 OF 1	SIZE A4
DGN	AMY	91.02.22			
DRW	SHIEH	91.02.22			