



P.C.B. RECOMMEND LAYOUT
(BOTTOM VIEW)

NOTES:

1. MATERIAL :
HOUSING : THERMOPLASTIC, GLASS FIBER FILLED
UL 94V-0 RATED.
CONTACT : PHOSPHOR BRONZE
OUTER SHIELD : SPCC
INNER SHIELD : SPCC
2. FINISH :
CONTACT : UNDER PLATED 50u"MIN. NICKEL ,OVER ALL
120u" MIN. TIN IN SOLDERING AREA,
SELECTIVE GOLD PLATED IN CONTACT AREA.
OUTER SHIELD : L:BRIGHT TIN , PLATED WITH 120u"THICK,
OVER 50u" THICKNESS Ni.
S: TIN , PLATED WITH 120u"THICK.
OVER 100u" THICKNESS Cu.
N:NICKEL , PLATED WITH 120u"THICK.
OVER 100u" THICKNESS Cu.
G: TIN , PLATED WITH 120u"THICK,
OVER 100u" THICKNESS Cu.
INNER SHIELD : L:BRIGHT TIN , PLATED WITH 120u"THICK.
OVER 50u" THICKNESS Ni.
S: TIN , PLATED WITH 120u"THICK.
OVER 100u" THICKNESS Cu.
N:NICKEL , PLATED WITH 120u"THICK.
OVER 100u" THICKNESS Cu.
G: GOLD FLASH , OVER 100u" THICKNESS Cu.

尚益科技有限公司 JMSCONN TECHNOLOGY CO., LED.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30010-5-03		
APP			MODEL	FILE NO	REV. X1
CHK	CCJ	91.01.16	UNIT MM	SHT 1 OF 1	SIZE A4
DGN	AMY	91.01.16			
DRW	SHIEH	91.01.16			