



P.C.B. RECOMMEND LAYOUT
(BOTTOM VIEW)

- NOTES:
1. MATERIAL :
HOUSING : THERMOPLASTIC, GLASS FIBER FILLED
 UL 94V-0 RATED.
CONTACT : PHOSPHOR BRONZE
OUTER SHIELD : SPCC
INNER SHIELD : SPCC
 2. FINISH :
CONTACT : UNDER PLATED 50u"MIN. NICKEL ,OVER ALL
 120u" MIN. TIN IN SOLDERING AREA,
 SELECTIVE GOLD PLATED IN CONTACT AREA.
OUTER SHIELD : L: BRIGHT TIN , PLATED WITH 120u"THICK,
 OVER 50u" THICKNESS Ni.
 S: TIN , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 N: NICKEL , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 G: TIN , PLATED WITH 120u"THICK,
 OVER 100u" THICKNESS Cu.
INNER SHIELD : L: BRIGHT TIN , PLATED WITH 120u"THICK.
 OVER 50u" THICKNESS Ni.
 S: TIN , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 N: NICKEL , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 G: GOLD FLASH , OVER 100u" THICKNESS Cu.

尚益科技有限公司
JMSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG		MOLD NO 30010-6-03	
APP				MODEL	FILE NO
CHK	CCJ	91.01.16			REV. X1
DGN	AMY	91.01.16		UNIT	SIZE
DRW	SHIEH	91.01.16		MM	A4
				UNIT	SHT 1 OF 1