



P.C.B. RECOMMEND LAYOUT
(BOTTOM VIEW)

- NOTES:
- MATERIAL :
 HOUSING : THERMOPLASTIC, GLASS FIBER FILLED
 UL 94V-0 RATED.
 CONTACT : PHOSPHOR BRONZE
 OUTER SHIELD : SPCC
 INNER SHIELD : SPCC
 - FINISH :
 CONTACT : UNDER PLATED 50u"MIN. NICKEL ,OVER ALL
 120u" MIN. TIN IN SOLDERING AREA,
 SELECTIVE GOLD PLATED IN CONTACT AREA.
 OUTER SHIELD : L:BRIGHT TIN , PLATED WITH 120u"THICK,
 OVER 50u" THICKNESS Ni.
 S:TIN , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 N:NICKEL , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 G:TIN , PLATED WITH 120u"THICK,
 OVER 100u" THICKNESS Cu.
 INNER SHIELD : L:BRIGHT TIN , PLATED WITH 120u"THICK.
 OVER 50u" THICKNESS Ni.
 S:TIN , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 N:NICKEL , PLATED WITH 120u"THICK.
 OVER 100u" THICKNESS Cu.
 G: GOLD FLASH , OVER 100u" THICKNESS Cu.

尚益科技有限公司
JMCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30010-8-04		
APP			MODEL	FILE NO	REV. X1
CHK	CCJ	91.01.16	UNIT MM	SHT 1 OF 1	SIZE A4
DGN	AMY	91.01.16			
DRW	SHIEH	91.01.16			