



NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	P.B.T.	BLACK	1	
2	CONTACT	PHOS. BRONZE	GOLD-TIN PLATED	4	N1:1~5u ; TIN:3u GOLD:1~3 u"
3	SHIELD	COPPER ALLOY	TIN-LEAD PLATED	1	TIN/LEAD:3~5u
4	BACK COVER	P.B.T.	BLACK	1	



REQUIREMENTS
 CONTACT RESISTANCE:30mΩmax.(INITIAL)
 INSULATION RESISTANCE:100MΩmin.AT 500V DC.
 WITHSTANDING VOLTAGE:500V AC FOR ONE MINUTE
 SOLDERING HEAT TEST:260±5°C FOR 5±1 SECONDS
 INSERTION FORCE:0.5~4.5KG
 EXTRACTION FORCE:0.4~3.5 KG
 LIFE TIME:5000 CYCLES min



尚益科技有限公司 JMISCONN TECHNOLOGY CO., LED.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30020-04-02		
APP			MODEL 4 pin	FILE NO MINI DIN JACK FULL SHIELD	REV. X1
CHK	CCJ	91.01.09	UNIT MM	SHT 1 OF 1	SIZE A4
DGN	WU	91.01.09			
DRW	SHIEH	91.01.09			