



P.C.B. RECOMMEND LAYOUT  
(BOTTOM VIEW)

- NOTES:
- MATERIAL  
HOUSING : THERMOPLASTIC, GLASS FIBER FILLED  
UL 94V-0 RATED.  
CONTACT : PHOSPHOR BRONZE  
SHIELD : BRASS  
GROUNDING: STAINLESS STEEL
  - FINISH  
CONTACT : UNDER PLATED 50 $\mu$ "MIN. NICKEL COVER ALL  
120 $\mu$ " MIN. TIN IN SOLDERING AREA  
SELECTIVE GOLD PLATED IN CONTACT AREA.  
SHIELD : (L)BRIGHT TIN , PLATED WITH 120 $\mu$ "THICK.  
OVER 50 $\mu$ "THICKNESS Ni.  
(S)TIN , PLATED WITH 120 $\mu$ "THICK,  
OVER 100 $\mu$ "THICKNESS Cu.  
(N)NICKEL , PLATED WITH 120 $\mu$ "THICK,  
OVER 100 $\mu$ "THICKNESS Cu.

尚益科技有限公司  
JMSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30025-3-03		
APP			MODEL	FILE NO	REV. X1
CHK	CCJ	91.01.16			
DGN	AMY	91.01.16	UNIT		SIZE A4
DRW	SHIEH	91.01.16	MM	SHT 1 OF 1	