



RECOMMENDED P.C.B LAYOUT  
(BOTTOM VIEW)

NOTE:

1. MATERIAL :

HOUSING : THERMOPLASTIC, GLASS FIBER FILLED  
UL 94V-0 RATED.  
CONTACT : PHOSPHOR BRONZE  
SHIELD : BRASS

2. FINISH :

CONTACT : UNDER PLATED 50u"MIN. NICKEL, OVER ALL  
120u" MIN. TIN IN SOLDERING AREA,  
SELECTIVE GOLD PLATED IN CONTACT AREA.  
SHIELD : L: BRIGHT TIN, PLATED WITH 120u"THICK.  
OVER 50u"THICKNESS Ni.  
S: TIN, PLATED WITH 120u"THICK.  
OVER 100u"THICKNESS Cu.  
N: NICKEL, PLATED WITH 120u"THICK.  
OVER 100u"THICKNESS Cu.

尚益科技有限公司  
JMSCONN TECHNOLOGY CO., LTD.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 30200-66-03S		
APP			MODEL	FILE NO	REV. X1
CHK					
DGN			UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2016.01.16	MM		