



APPLICATION AND FEATURES
 1. LOW-PROFILE PIN HEADERS ARE DESIGNED AS MATING DEYLES FOR IDC SOCKET (PLA FCS-SERIES CONNECTOR)
 2. ASSURES RELIABLE FLAT CABLE-10 P.C.B INTERCONNECTION
 3. FULLY SHROUNDED
 4. NO EJECTOR LATCHES IS FOR SAVING SPACE

SPECIFICATIONS
 CURRENT RATING: 1 AMP
 INSULATOR RESISTANCE: 5000 MEGOHMS MIN
 500V DC FOR 1MINUTES
 DIELECTRIC WITHSTANDURE: AC 500V FOR 1MINUTES
 OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 CONTACT MATERIAL: BRONZE OR PHOSPHOR BRONZE
 INSULATOR MATERIAL: NYLON UL 94V-0 STANDARD NYLON-46

CONTACT RESISTANCE: $300\text{m}\Omega$ AT DC 100MA
 INSULATION RESISTANCE: $1000\text{m}\Omega$ Min at DC 500V

POS	DIM		
	A	B	C
6	15.24	12.94	5.08
8	17.78	15.48	7.62
10	20.35	18.01	10.16
12	22.86	20.56	12.70
14	25.40	23.10	15.24
16	27.94	25.64	17.78
20	33.05	30.75	22.86
24	38.72	35.92	27.94
26	40.76	38.46	30.48
30	45.84	43.54	35.56
34	51.15	48.90	40.64
40	58.67	56.24	48.26
44	63.62	61.32	53.34
50	71.24	68.94	60.96
60	84.00	81.40	73.66
64	89.04	86.74	78.74

尚益科技有限公司
 JMSSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 13500
APP		92.04.10	MODEL P:2.54MM
CHK	CCJ	91.01.22	FILE NO BOX HEADER
DGN	AMY	91.01.22	UNIT MM
DRW	SHIEH	91.01.22	SHT 1 OF 1
			REV. X1
			SIZE A4