



APPLICATION AND FEATURES

1. LOW-PROFILE PIN HEADERS ARE DESIGNED AS MATING DEVICES FOR IDC SOCKET (PLA FCS-SERIES CONNECTOR)
2. ASSURES RELIABLE FLAT CABLE-10 P.C.B INTERCONNECTION
3. FULLY SHROUDED
4. NO EJECTOR LATCHES IS FOR SAVING SPACE

SPECIFICATIONS

CURRENT RATING	1 AMPS
INSULATOR RESISTANCE	5000 MEGOHMS MIN
DIELECTRIC WITHSTANDING	500 V DC FOR 1MINUTES
OPERATING TEMPERATURE	AC 500 V FOR 1MINUTERS
CONTACT MATERIAL	-40°C~+105°C
INSULATOR MATERIAL	BRONZE OR PHOSPHOR BRONZE
	NYLON UL 94V-0 @STANDARD NYLON-46

POS	DIM		
	A	B	C
4 pin	11.02	2.00	10.00
6 pin	13.07	4.00	12.02
8 pin	15.08	6.00	14.08
10 pin	17.05	8.00	16.08
12 pin	19.03	10.00	18.08
14 pin	21.05	12.00	20.08
20 pin	27.14	18.00	25.15
24 pin	31.20	22.00	30.20
26 pin	33.09	24.00	32.16

POS	DIM		
	A	B	C
30 pin	37.20	28.00	36.18
32 pin	39.20	30.00	38.20
34 pin	41.20	32.00	40.21
36 pin	43.21	34.00	42.22
40 pin	47.26	38.00	46.20
44 pin	51.26	42.00	50.26
50 pin	57.29	48.00	56.25

尚益科技有限公司
JMSSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 13600
APP		MODEL	FILE NO
CHK	CCJ	91.01.02	P:2.00mm BOX HEADER
DGN	AMY	91.01.02	REV. X1
DRW	SHIEH	91.01.02	UNIT MM
			SHT 1 OF 1
			SIZE A4