

ORDER INFORMATION:



PART NO:	CONTACTS PLATING	COLOR
20001-TBAB	GOLD/TIN PLATED	WHITE
20001-TBAW	GOLD/TIN PLATED	BLACK

ELECTRICAL CHARACTERISTICS :  
 CONTACT CURRENT RATING : 1.5 AMPERES.  
 VOLTAGE RATING : 30V R.M.S MAXIMUM.  
 DIELECTRIC WITHSTANDING VOLTAGE : AC 500V R.M.S.  
 INSULATION RESISTANCE : 1000 MEGOHMS MINIMUM  
 AT DC 500V.  
 CONTACT RESISTANCE : 30m OHMS MAXIMUM.  
 OPERATING TEMPERATURE RANGE : 0°C TO +50°C  
 CONTACT INSERTION FORCE : 3.50 KG MAXIMUM.  
 CONTACT SEPARATION FORCE : 1.00 KG MINIMUM.

MATERIALS :  
 CONTACT : COPPER ALLOY.  
 INSULATOR : P.B.T.U.L 94-VD RATED/LCP  
 SHELL : BRASS/SPCC

FINISHES :  
 CONTACTS : AU 10 $\mu$ , 30 $\mu$ , 50 $\mu$ , 100 $\mu$ , 150 $\mu$ , 300 $\mu$  PLATED ON  
 CONTACT AREA, 100-120 $\mu$  SN PLATED ON  
 SOLDER TAIL POINT BOTH OVER 50 $\mu$  MIN  
 NI UNDERPLATED OVERALL

SHELL :  
 BRASS MATERIAL: 50 $\mu$  NICKEL PLATED OVERALL.  
 SPCC MATERIAL: PLATED 50 $\mu$  NICKEL, CU 80 $\mu$  MIN  
 UNDERPLATED OVERALL.

 尚益科技 尚益科技有限公司 JMSCONN TECHNOLOGY CO., LTD.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO	20001-TBA	
APP			MODEL	FILE NO	REV. X1
CHK			UNIT	SHT 1 OF 1	SIZE A4
DGN			MM		
DRW	HSIEH	2016.11.16			