



1.Material:

Contacts:Phosphore Bronze
 Insulalor:PBT+30% G.F UL 94V-0
 Shell:BRASS

2.Mechanical:

Mating:35N max
 Withdrawal Force:10N min
 Durability:1500 cycles min.

3.Electrical:

Current-max[amps] 1.5A
 Voltage-max[volls] 30V
 Withslonding Voltage 750V AC
 Contact Resistance[ohms] 30 milliohms max
 Insulation Resistance[ohms] 1000 Megohms min

4.Plating:

Contacts:Gold And Tin Over Nickel Plated
 Shell: Nickel over all plating

5.Environmental

Temperature Rong -55°C TO +85°C

6.重點管控尺寸[XX].

Plat No.	Color	INSULATOR
20030-TWP	WHITE	PBT
20030-TWN	WHITE	NY-6T
20030-TBN	BLACK	NY-6T
20030-TBP	BLACK	PBT

尚益科技有限公司
 JMSCONN TECHNOLOGY CO., LTD.

PROJ		SCALE : F DO NOT SCALE DWG		MOLD NO 20030-T	
APP		MODEL	FILE NO	REV.	
CHK		AW	USB.TYPE A180°DIP	X1	
DGN		UNIT	SHT 1 OF 1	SIZE	
DRW	HSIEH	MM		A4	
			2016.11.16		