



**MATERIALS**

- 1.HOUSING:HI-TEMP.PLASTIC(UL 94V-0),BLACK.
- 2.TERMINAL:COPPER ALLOY.(t=0.25mm)
- 3.SHELL:BRASS.TIN PLATING(t=0.40mm)

**SPECIFICATION**

- 1.CURRENT RATING:1AMP.MAX.
- 2.DIELECTRIC WITHSTANDING VOLTAGE:  
30V AC R.M.S FOR ONE VOLTAGE
- 3.INSULATION RESISTANCE:100M OHMS MIN. AT 100V DC.
- 4.CONTACT RESISTANCE:50m OHMS MAX.
- 5.OPERATING TEMPERATURE:20°C TO+85°C
- 6.DURABILITY:5000CYCLE
- 7.MATING FORCE:3.5kgs MAX
- 8.UNMATING FORCE:0.7kgs MIN
- 9.MAX PROCESSING TEMP:230°C FOR30~60 SECONDS

尚益科技有限公司  
JMSCONN TECHNOLOGY CO., LED.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 20081-X-04		
APP			MODEL	FILE NO	REV.
CHK	CCJ	91.06.17	5 PIN	MINI USB P.C.B. MOUNT BTYPE SMT METAL SHIELD,FEMALE	X1
DGN	AMY	91.06.17	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	91.06.17	MM		A4