



Green Product

**Specification:**

- \*Contact Resistance:
  - (1)30m Ohm Max. at 100mA
  - (2)10,000 Cycles After: 40m Ohm Max.at 100mA
- \*Rated Voltage: AC 30V
- \*Contact Current Rating:
  - (1)Signal Line: 1A/Pin (No. 1 to 5)
  - (2)2-Line For Power: 1.8A/Pin(No. 1 and 5),0.5A/Pin(No. 2 to 4)
- \*Insulation Resistance: 100M Ohm Min. At 500V DC
- \*Dielectric Withstanding Voltage: 100V AC for 1 Minute
- \*Durability (Life Test): 10,000 Cycles Front
- \*Insertion Force: 35 Newton Maximum
- \*Extraction Force: 8 Newton Minimum.
- \*Operating Temperature: -30°C to +80°C
- \*Solderability: 260°C±5°C;5 Sec

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	LCP+GF30%	BLACK	1	
2	PIN TERM.	PHOS.BRONZE(EH) t:0.20mm	GOLD PLATED	5	All Area: Gold 1u'
3	SHELL	STAINLESS T=0.25	TIN PLATED(MATTE Sn)	1	TIN: 120~200u"

尚益科技有限公司					
JMSCONN TECHNOLOGY CO., LTD.					
PROJ		SCALE : F	MOLD NO	20084-S4	
		DO NOT SCALE DWG			
APP			MODEL	FILE NO	REV.
CHK	<b>HSIEH</b>	<b>2011.02.09</b>			X1
DGN	<b>HSIEH</b>	<b>2011.02.09</b>	UNIT	SHT 1 OF 1	SIZE
DRW	<b>HSIEH</b>	<b>2011.02.09</b>	MM		A4