



Green Product

RECOMMENDED PCB LAYOUT

Specification:
 Contact Resistance: 50m Ohm. Max.
 Insulation Resistance: 100M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1A At 30VAC Minimum.
 Dielectric Withstanding Voltage: 100V AC for 1 Minute
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 3 Newton Minimum.
 Durability (Life Test): 3000 Cycles

PACKING STYLE: TAPE REELING WITH MYLAR TAPE

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	LCP+ G.F.30%	BLACK	1	
2	PIN TERM.	PBS T:0.2	GOLD PLATED	8	Contact : Gold 15u" Other Area: Gold 1u"
3	SHELL	BRASS T:0.3	NICKEL PLATED	1	Ni:80~120u"
4	MYLAR TAPE	MYLAR	YELLOW	1	

尚益科技有限公司 JMSSCONN TECHNOLOGY CO., LTD.					
PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 20086		
APP			MODEL	FILE NO	REV. X1
CHK					
DGN			UNIT	SHT 1 OF 1	SIZE A4
DRW	HSIEH	2016.02.14	MM		