



Specification  
 1. Current Rating: 0.5A AC/DC  
 2. Voltage Rating: 30V AC/DC  
 3. Contact Resistance: 20mΩ Max.  
 4. Insulation Resistance: 100MΩ Min.  
 5. Withstand Voltage: AC200V/Minute  
 6. Operating Temperature: -25 C ~ +85 C

Material:  
 1. Housing: Thermoplastic UL94V-0  
 2. Contact Pin: Copper Alloy T=0.15  
 3. Tab: Copper Alloy T=0.2  
 Finish:  
 1. Housing: Natural  
 2. Contact Pin: Gold Plated  
 3. Tab: Gold Plated  
 Part No. 40080-1-XX A C 8 0  
 No. Of Pin: 02~08  
 Packing: 8:T&R With Mylor  
 Housing Material: A:LCP UL94V-0 Natural  
 Plating: C:Gold Plated

PIN	DIM.A	DIM.B	DIM.C	DIM.D	PIN	DIM.A	DIM.B	DIM.C	DIM.D
02	0.80	1.90	3.78	3.04	06	4.00	5.10	6.98	6.24
03	1.60	2.70	4.58	3.84	07	4.80	5.90	7.78	7.04
04	2.40	3.50	5.38	4.64	08	5.60	6.70	8.58	7.84
05	3.20	4.30	6.18	5.44					

**尚益科技有限公司**  
 JMSCONN TECHNOLOGY CO., LTD.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO 40080-1		
APP			MODEL	FILE NO	REV. X1
CHK			UNIT	SHT 1 OF 1	SIZE A4
DGN			MM		
DRW	HSIEH	2017.10.20			